HANSA

HANSA

Installation and maintenance guide








4-8

8861 9045

I (ISO 3822)
EN 1111
100 - 1000 kPa
0.38 l/s (300 kPa)
max. +80°C










mpi.hansa.com/88619045

8862 9045 , **8862** 3045

I (ISO 3822)
EN 1111
100 - 1000 kPa
0.37 / 0.37 l/s (300 kPa)
max. +80°C










mpi.hansa.com/88629045

8113 9552

EN 1111
50 - 1000 kPa
0.38 l/s (300 kPa)
max. +90°C










mpi.hansa.com/81139552

8114 9552 , **8114** 3552

EN 1111
50 - 1000 kPa
0.37 / 0.37 l/s (300 kPa)
max. +90°C










mpi.hansa.com/81149552

8113 9562 , **8113** 9562 33

EN 1111
100 - 1000 kPa
0.38 l/s (300 kPa)
max. +90°C










mpi.hansa.com/81139562

8114 9562 , **8114** 9562 33 , **8114** 3562

EN 1111
100 - 1000 kPa
0.34 / 0.34 l/s (300 kPa)
max. +90°C









mpi.hansa.com/81149562

8113 9572

I (ISO 3822)
EN 1111
50 - 1000 kPa
0.38 l/s (300 kPa)
100 kPa (0.2 l/s)
max. +80°C







mpi.hansa.com/81139572

8114 9572

I (ISO 3822)
EN 1111
50 - 1000 kPa
0.34 / 0.2 l/s (300 kPa)
100 kPa (0.2 l/s)
300 kPa (0.3 l/s)
max. +90°C







mpi.hansa.com/81149572

8112 9583

I (ISO 3822)
EN 1111
50 - 1000 kPa
0.49 l/s (300 kPa)
max. +90°C







mpi.hansa.com/81129583

HANSA

8114 3572

I (ISO 3822)
EN 1111
50 - 1000 kPa
0.34 / 0.2 l/s (300 kPa)
300 kPa (0.2 l/s)
300 kPa (0.3 l/s)
max. +90°C







mpi.hansa.com/81143572

8860 9045

I (ISO 3822)
EN 1111
100 - 1000 kPa
0.40 l/s (300 kPa)
max. +80°C







mpi.hansa.com/88609045

8866 9501

I (ISO 3822)
EN 1111
50 - 1000 kPa
0.42 l/s (300 kPa)
max. +90°C







mpi.hansa.com/88669501

8112 9573

EN 1111
50 - 1000 kPa
0.42 l/s (300 kPa)
max. +90°C





mpi.hansa.com/81129573

Oras Group is a powerful European provider of sanitary fittings: the market leader in the Nordics and a leading company in Continental Europe. The company's mission is to make the use of water easy and sustainable and its vision is to become the European leader of advanced sanitary fittings. Oras Group has two strong brands: Oras and Hansa.

The Group's head office is located in Rauma, Finland, and the Group has three manufacturing sites: Kralovice (Czech Republic), Olesno (Poland) and Rauma (Finland). Oras Group employs approximately 1,200 people in twenty countries. Oras Group is owned by Oras Invest, a family company and an industrial owner.

943247D-01-21

HANSA Armaturen GmbH
P. O. BOX 81 02 40
D-70519 Stuttgart
Sigmaringer Strasse 107
D-70567 Stuttgart
Tel.: +49 711 16 14 0
Fax: +49 711 16 14 368
info@hansa.de
www.hansa.com

HANSA