FRAME 25 MIRROR CABINET

Mirror cabinet with LED light

40830.1 / 40830.2 40831.1 / 40831.2

40831.1 / 40831.2 40832.1 / 40832.2

40835.1 / 40835.2

40836.1 / 40836.2

40837.1 / 40837.2



TECHNICAL DATA


Order	no
-------	----


- 40830.1 / door hinge left, with sensor switch, 2 sockets (EU)
- 40831.1 / door hinge left, hardwired for room switch, 2 sockets (CH)
- 40832.1 / door hinge left, hardwired for room switch
- 40835.1 / door hinge left, bottom ambient light, with sensor switch, 2 sockets (EU)
- 40836.1 / door hinge left, hardwired for room switch, bottom ambient light with sensor switch, 2 sockets (CH)
- 40837.1 / door hinge left, hardwired for room switch, bottom ambient light with sensor switch, without sockets
- 40830.2 / door hinge right, with sensor switch, 2 sockets (EU)
- 40831.2 / door hinge right, hardwired for room switch, 2 sockets (CH)
- 40832.2 / door hinge right, hardwired for room switch
- 40835.2 / door hinge right, bottom ambient light, with sensor switch, 2 sockets (EU)
- 40836.2 / door hinge right, hardwired for room switch, bottom ambient light with sensor switch, 2 sockets (CH)
- 40837.2 / door hinge right, hardwired for room switch, bottom ambient light with sensor switch, without sockets

Certified to	IP44


Dimensions (WxHxD)	450 x 750 x 150 mm
Specification	Body - Inner part anodized aluminum (sidewall
	top, bottom), back wall grey melamine coated MDF
	Door - Glass 3+3 mm
	1 door with inside and outside mirrors, including
	handle (optional usable)
	With vertical LED light
	2x 14W/m, 4000 Kelvin (daylight), IP44, 230V
	3 glass shelves (adjustable)
Weight	14,0 kg
Accessories excl.	Accessories set consisting of 1 organizer,
	cosmetic mirror and magnetic bar self adhesive,
	order no. 49060.0
Mounting acc. incl.	Installation set, order no. 49063.0
Mounting acc. excl.	Installation frame set for mirror cabinet 450 mm,
	aluminium, dimensions 480 x 780 x 30 mm,
	order no. 40838.0 (only 40830.1, 40831.1,
	40832.1, 40830.2, 40831.2, 40832.2 in connection
	with colour option 144)
Mounting information	The fortification walls must meet the requirements
	of the furniture in terms of weight and the
	supplied fasteners. This can not be guaranteed,
	another method of attachment is chosen.
	230V power supply required.
	Attention: Clearance for sensor switch
	min. 15 cm below mirror cabinet!
Colours side wall	144 - Mirror, 145 - Glass with white backing

TECHNICAL DRAWINGS / S 1 : 20





(cover)



LAUFEN